


Grange Tubes

PTFE extruded products

PTFE Spiral Binding - GTB



- ID Internal Diameter
- W Width of Strip
- T Thickness of Strip

Service Temp. Range	-70°C to +260°C
Shelf Life	N/A
Chemical Resistance	Virtually total
Water Absorption	0.01%
Flammability	Non-flammable UL94 Rating V-0
Dielectric Strength	19.7kV/mm
Tensile Strength	Longitudinal 33 N/mm ² Transverse 31 N/mm ²
Shore Hardness	D55
Colour Range	Black as standard, other colours from our full range available on request.
Packaging	Reels or coils
Applicable Standards	PAN 6480 - AS41088
Value Added Services	Cut lengths.

Part Code	ID mm	W mm	T mm	Weight g/m	Package
GTB30	3.0 ± .25	5.0 ± .25	0.75 ± .08	20	100m Reel
GTB50	5.0 ± .40	5.0 ± .25	0.75 ± .08	29	50m Reel
GTB75	7.5 ± .50	8.0 ± .40	0.75 ± .08	40	30m Reel
GTB100	10.0 ± .75	8.0 ± .40	0.75 ± .08	50	15m Bag
GTB125	12.5 ± .80	10.0 ± .50	0.75 ± .08	67	15m Bag
GTB200	20.0 ± .80	12.5 ± .65	1.25 ± .10	210	Bag
GTB255	25.5 ± .80	12.5 ± .65	1.25 ± .10	250	Bag

Note: This product may become distorted during storage and transit, we would advise gentle heating (not exceeding 100°C would be sufficient) to return the product to its natural state.

