


# Grange Tubes

PTFE extruded products

## Metric PTFE Tubing



- Service Temp. Range** -70°C to +260°C
- Shelf Life** N/A
- Chemical Resistance** Virtually total
- Water Absorption** 0.01%
- Flammability** Non-flammable UL94 Rating V-0
- Dielectric Strength** 19.7kV/mm
- Tensile Strength** Longitudinal 33 N/mm<sup>2</sup> Transverse 31 N/mm<sup>2</sup>
- Shore Hardness** D55
- Colour Range** Natural as standard, other colours from our full range available on request.
- Packaging** Reels or coils. Please contact us for any special packaging requirements.
- Applicable Standards** BS 2848 Type 6 Class 250T; BS EN 60684; BS 6564; BS EN ISO 13000
- Value Added Services** Cut lengths; cut pieces (up to 10mm OD/2mm Wall); spiral cutting (up to 10mm OD/1mm Wall); flared & tafted ends; punched & drilled holes

Part Code	ID mm	OD mm	MOQ (m)
1X2	1.00 ± 0.10	2.00 ± 0.13	300
1X2.5	1.00 ± 0.08	2.50 ± 0.13	400
1X3	1.00 ± 0.08	3.00 ± 0.10	150
1X6	1.00 ± 0.08	6.00 ± 0.20	60
2X3	2.00 ± 0.10	3.00 ± 0.10	200
2X4	2.00 ± 0.10	4.00 ± 0.10	100
2X5	2.00 ± 0.13	5.00 ± 0.20	100
2X6	2.00 ± 0.13	6.00 ± 0.10	60
2.5X4	2.50 ± 0.08	4.00 ± 0.08	200
3X4	3.00 ± 0.08	4.00 ± 0.08	150
3X4.5	3.00 ± 0.08	4.50 ± 0.08	200
3X5	3.00 ± 0.10	5.00 ± 0.13	100
3X6	3.00 ± 0.13	6.00 ± 0.20	50
3.5X5.5	3.50 ± 0.10	5.50 ± 0.13	100
4X5	4.00 ± 0.20	5.00 ± 0.20	100
4X5.5	4.00 ± 0.08	5.50 ± 0.10	150
4X6	4.00 ± 0.15	6.00 ± 0.20	50
5X6	5.00 ± 0.20	6.00 ± 0.15	100
5X6.5	5.00 ± 0.15	6.50 ± 0.15	150
5X7	5.00 ± 0.20	7.00 ± 0.20	50
5X8	5.00 ± 0.20	8.00 ± 0.20	50
5.5X8	5.50 ± 0.20	8.00 ± 0.20	60
6X7	6.00 ± 0.20	7.00 ± 0.20	100
6X8	6.00 ± 0.20	8.00 ± 0.20	50
6X9	6.00 ± 0.20	9.00 ± 0.20	50
7X10	7.00 ± 0.20	10.00 ± 0.20	30
8X9	8.00 ± 0.20	9.00 ± 0.20	50
8X10	8.00 ± 0.20	10.00 ± 0.25	30
8X12	8.00 ± 0.25	12.00 ± 0.25	30
9X10	9.00 ± 0.20	10.00 ± 0.20	50
9X12	9.00 ± 0.25	12.00 ± 0.25	30
10X11	10.00 ± 0.20	11.00 ± 0.25	50
10X12	10.00 ± 0.20	12.00 ± 0.25	30
12X14	12.00 ± 0.25	14.00 ± 0.25	30
12X15	12.00 ± 0.25	15.00 ± 0.25	30

