


Grange Tubes

PTFE extruded products

Metric PTFE Rod



Service Temp. Range	-70°C to +260°C
Shelf Life	N/A
Chemical Resistance	Virtually total
Water Absorption	0.01%
Flammability	Non-flammable UL94 Rating V-0
Dielectric Strength	19.7kV/mm
Tensile Strength	Longitudinal 33 N/mm ² Transverse 31 N/mm ²
Shore Hardness	D55
Colour Range	12 colours including natural
Packaging	Reels or coils.
Applicable Standards	BS 6564; BS EN ISO 13000
Value Added Services	Cut lengths; cut pieces.

Part Code	OD mm	MOQ m
1.00	1.00 ± .10	2000
1.50	1.50 ± .10	900
2.00	2.00 ± .10	500
2.50	2.50 ± .10	300
3.00	3.00 ± .10	200
3.50	3.50 ± .10	150
4.00	4.00 ± .10	120
4.50	4.50 ± .10	100
5.00	5.00 ± .10	80
5.50	5.50 ± .10	70
6.00	6.00 ± .15	50
6.50	6.50 ± .15	50
7.00	7.00 ± .15	40
7.50	7.50 ± .15	30
8.00	8.00 ± .15	30
8.50	8.50 ± .15	25
9.00	9.00 ± .20	20
9.50	9.50 ± .20	20
10.00	10.00 ± .20	20

