


Grange Tubes

PTFE extruded products

PTFE Heat Shrink 2:1 - HST



D Expanded ID
d Recovered ID
W Recovered Wall

Shrink Temperature	350°C ± 5°C
Shelf Life	PTFE Heat Shrink conforming to AMS-DTL-23053/12 specifies a shelf life of 4 years when stored at 18 to 35°C
Chemical Resistance	Virtually total.
Water Absorption	0.01%
Flammability	Non-flammable UL94 Rating V-0
Service Temp. Range	-70°C to +260°C
Dielectric Strength	19.7kV/mm
Colour Range	12 colours including natural.
Packaging	Reels or 1.22m cut lengths.
Applicable Standards	AMS-DTL-23053/12 Class 3
Value Added Services	Cut lengths.

Part Code	D Min		d Max		W		Package	
	Inches	mm	Inches	mm	inches	mm	Reel	1.22m Lengths
HST24	.050	1.27	.027	0.69	.010±.002	.25±.05	100m	50pcs
HST22	.055	1.40	.032	0.81	.012±.003	.30±.07	100m	50pcs
HST20	.060	1.52	.039	0.99	.012±.003	.30±.07	100m	50pcs
HST18	.076	1.93	.049	1.24	.012±.003	.30±.07	100m	50pcs
HST16	.093	2.36	.061	1.55	.012±.003	.30±.07	100m	50pcs
HST14	.120	3.05	.072	1.83	.012±.003	.30±.07	100m	50pcs
HST12	.150	3.81	.089	2.26	.012±.003	.30±.07	100m	50pcs
HST10	.191	4.85	.112	2.84	.012±.003	.30±.07	50m	50pcs
HST08	.240	6.10	.141	3.58	.015±.004	.38±.10	50m	25pcs
HST06	.302	7.67	.178	4.52	.015±.004	.38±.10	50m	25pcs
HST05	.320	8.13	.198	5.03	.015±.004	.38±.10	50m	25pcs
HST04	.370	9.40	.224	5.69	.015±.004	.38±.10	50m	10pcs
HST03	.390	9.91	.249	6.32	.015±.004	.38±.10	50m	10pcs
HST02	.410	10.41	.260	6.60	.015±.004	.38±.10	30m	10pcs
HST01	.450	11.43	.311	7.90	.015±.004	.38±.10	30m	10pcs
HST00	.470	11.94	.347	8.81	.015±.004	.38±.10	30m	10pcs

