


# Grange Tubes

PTFE extruded products

## PTFE Heat Shrink 4:1 - HST-R



D Expanded ID  
d Recovered ID  
W Recovered Wall

- Shrink Temperature** 350°C ± 5°C
- Shelf Life** PTFE Heat Shrink conforming to AMS-DTL-23053/12 specifies a shelf life of 4 years when stored at 18 to 35°C
- Chemical Resistance** Virtually total.
- Water Absorption** 0.01%
- Flammability** Non-flammable UL94 Rating V-0
- Service Temp. Range** -70°C to +260°C
- Dielectric Strength** 19.7kV/mm
- Colour Range** 12 colours including natural.
- Packaging** Reels or 1.22m cut lengths.
- Applicable Standards** AMS-DTL-23053/12 Class 5
- Value Added Services** Cut lengths.

Part Code	D Min		d Max		W		Package	
	Inches	mm	Inches	mm	inches	mm	Reel	1.22m Lengths
HST-R1/8	.125	3.18	.037	.94	.012±.002	.30±.05	100m	50pcs
HST-R3/16	.187	4.75	.050	1.27	.012±.002	.30±.05	100m	50pcs
HST-R1/4	.250	6.35	.063	1.60	.012±.002	.30±.05	100m	50pcs
HST-R5/16	.312	7.92	.078	1.98	.012±.002	.30±.05	100m	50pcs
HST-R3/8	.375	9.53	.096	2.44	.012±.002	.30±.05	100m	50pcs
HST-R7/16	.438	11.13	.112	2.84	.012±.002	.30±.05	100m	25pcs
HST-R1/2	.500	12.70	.144	3.66	.015±.004	.38±.10	50m	25pcs
HST-R9/16	.562	14.27	.155	3.94	.015±.004	.38±.10	50m	25pcs
HST-R5/8	.625	15.88	.178	4.52	.015±.004	.38±.10	50m	25pcs
HST-R11/16	.687	17.45	.198	5.03	.015±.004	.38±.10	50m	25pcs
HST-R3/4	.750	19.05	.224	5.69	.015±.004	.38±.10	50m	25pcs
HST-R7/8	.875	22.23	.244	6.20	.015±.004	.38±.10	50m	25pcs
HST-R1	1.000	25.40	.278	7.06	.015±.004	.38±.10	50m	25pcs
HST-R1¼	1.250	31.75	.347	8.81	.015±.004	.38±.10	50m	25pcs

