PTFE Convoluted

OD

Manufacturer

Country of Origin

Shelf Life & Storage

ID Min

mm

4.57

6.86

7.62

9.27

10.80

12.32

1549

18.54

21.59

24.77

30.99

in.

0 180

0.270

0.300

0.365

0.425

0.485

0.610

0.730

0.850

0.975

1.220

Applicable Standards

Material

HS Code

PART CODE

GT04-06

GT04-09

GT04-10

GT04-12

GT04-14

GT04-16

GT04-20

GT04-24


GT04-28

GT04-32

GT04-40

ECCN

Deep Convoluted – GT04



Pan 6627

39173200

ID Nom

UK

EU99

in.

0 187

0.281

0.312

0.375

0.437

0.500

0.625

0.750

0.875

1.000

1.250

Grange Tubes LLP

No special requirements

mm

4 7.5

7.14

7.92

9.53

11.10

12 70

15.88

19.05

22.23

25.40

31.75

PTFE - Polytetrafluoroethylene (CF2)ⁿ

OD Max

mm

8 26

10.80

11.56

12.83

14.61

16.00

19.56

23.37

27.43

30.73

38.10

in.

0.325

0.425

0.455

0.505

0.575

0.630

0 770

0.920

1.080

1.210

1.500

KEY **ID** - Internal Diameter **OD** – Outside Diameter MBR – Minimum Bend Radius **TPI – Turns Per Inch**

Wall

mm

0.46

0.56

0.61

0.66

0.66

0.69

0.76

0.76

0.81

0.89

in.

0.018

0.022

0.024

0.026

0.026

0.027

0.030

0.030

0.032

0.035

0.026 0.66

MBR

mm

6.35

9.53

10.16

12.70

15.24

17.15

25 40

27.94

31.75

35.56

40.64

in.

0 250

0.375

0.400

0.500

0.600

0.675

1 000

1.100

1.250

1.400

1.600

Pitch

0.125 3.18

0.125 3.18

mm

2.82

3.18

3.18

3.18

3 18

3.63

4.23

4.23

in.

0 1 1 1

0.125

0.125

0.125

0 1 2 5

0.143

0.167

0.167

0.200 5.08

Weight

g/m

34

59

78

84

104

106

128

190

250

262

338



APPLICATIONS

Our flexible helically formed PTFE Convoluted is widely used in the aerospace and automotive industries for cable harnessing. It is also used for fluid transfer, abrasion protection and thermal insulation. It is ideal for use in areas where there are hazardous chemicals and extreme temperatures.

SIZE RANGE

We produce a variety of different types of convoluted with bore sizes from 1.5mm to 38mm. GT01 - Light Wall GT02 - Shallow GT03 - Standard GT04 - Deep GTCRS - Crush Resistant SBC - Smooth Bore

COLOUR RANGE

Convoluted is available in black* as standard, other colours from our colour range are available on request. * SBC is available in natural only.

PACKAGING

Can be supplied in random lengths on reels or in coils as appropriate. Cut lengths are available along with other options such as cuffed or plugged ends. Please refer to the Value-Added Services section for the full range. If you have any special packaging requirements, please contact our sales team.

VALUE ADDED SERVICES

Cut lengths. Straightened ends Plugged ends. Cuffed ends Flared ends Punched & drilled holes. Slitting

PRODUCT COMPLIANCE

European Regulation (EC) No. 1907/2006 The Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) None of the Substances of Very High Concern (SVHC) included in the list of candidates for authorisation published by the European Chemicals Agency are present in concentrations greater than those permitted in any of the products manufactured and supplied by Grange Tubes LLP. Directive (EU) 2017/2102 amending Directive 2011/65/EU - The Restriction of the use of certain Hazardous Substances in electrical and electronic equipment – RoHS3 None of the substances restricted by RoHS3 are present in quantities above those permitted within the regulation in any of the products manufactured and supplied by Grange Tubes LLP.

DISCLAIMER: The information in this Data Sheet is believed to be correct as of the date issued, no warranty is given as to the fitness of the Product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that such exclusion is permitted by law. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. The information is subject to change without notice and replaces and lada sheets previously supplication. Liability for loss or damage resulting from any relance on the Information or use of it (including liability resulting from negligence or where Grange Tubes LLP vas aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict Grange Tubes LLP's liability for death or personal injury resulting from its negligence.

👊 Grange Tubes +44 (0)15395 34233 | info@grange-tubes.co.uk | www.grange-tubes.co.uk | @Grange Tubes Nov-23